

- 多种外壳材质选择，有工程塑料、铁板、铝合金等；
Kinds of shell's material for choice, such as engineering plastic, steel panel, aluminium alloy, etc;
- 金属外壳采用强化烤漆喷塑表面，耐冲击、耐磨损、耐高温；
Metal shell use the strenghtening to reast the surface,bears the impact, the wearability,thermostable;
- 电缆引出设有电缆锁紧护套，可防水、防油；
Cable lock-in jacket is made for the cable coming out and it is waterproof, grease proofing;
- 开关底部设有橡胶脚垫，可防滑；
Switch bottom is equipped with the rubber pad,for skidproof;
- 广泛应用于各种工业自动化装置、搬运、冲压、医疗、测试等场合作控制用。
Widely used for control in industrial automation equipments, transport,pressing, medical treatment,test and etc.










◆型号含义 Model & Meanings



◆基本参数 Basic parameters

接触电阻 Contact resistance	25mΩ(初值 initial value)
绝缘电阻 Insulation resistance	100MΩ以上(Above) DC500V
介质耐压 Withstand voltage	≥2000VAC
机械寿命 Mechanical Life	1,000,000次以上 above
电气寿命 Electrical Life	100,000次以上 above
使用温度 Operating temperature	-20~+70℃
使用湿度 Operating Humidity	≤85%

◆触点形式 Contact Forms




◆使用注意事项 Application attentions

- 根据负载的性质和电流值的不同，请注意产品的额定负载，本系列产品分10A与15A；
According to the difference of load and current value, rated load should be taken note. Current value of this series is 10A and 15A;
- 搬运以及移动时请注意内部配线的短路、断路等现象发生；
When transporting and moving,pls take note of the short circuit or open circuit may happen in internal wiring;
- 使用在有大量水、油、粉尘等场所时请注意产品的防护等级，本系列产品分防护型与非防护型；
Please take note of the level of protection when used in water,oil and bug dust.This series has protective type and unprotective type;
- 重压和冲击是造成产品损坏的直接原因，请务必小心；
The immediate cause for broken is stress and attack,please pay attention;
- “当心触电”与“注意”警示标志提醒大家使用时注意人身安全与产品的正常使用。
Warning mark'Danger! High Voltage!' and'Take note!' remind us pay attention to personnel safety and correctly operation.


◆外形尺寸/技术参数 Dimensions/Specification

• XF-01




材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-1




材 质 Material	钢板(Steel)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×1m
防护等级 Protection Degree	IP54

• XF-2




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-3




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-201





材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-302





材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-402




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	-- ²
防护等级 Protection Degree	IP65

• XF-502





材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-302B




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-502B




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-4




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-101




材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.75mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-102




材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-103




材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	2C
引出电缆 Outgoing Cable	0.5mm ² ×6芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-201D





材 质 Material	ABS工程塑料(Plastic)+钢板(Steel)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C×2
引出电缆 Outgoing Cable	0.5mm ² ×6芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-1D





材 质 Material	钢板(Steel)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1A×2
引出电缆 Outgoing Cable	0.5mm ² ×4芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-1T




材 质 Material	钢板(Steel)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1A×3
引出电缆 Outgoing Cable	0.5mm ² ×6芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-502S




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XZ-15GW22-B
额定负载 Rating Load	15A/250VAC
触点形式 Contact Form	1C+1C
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-81




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-82




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm ² ×3芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-84





材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-85





材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1A×2
引出电缆 Outgoing Cable	0.5mm²×4芯(Wire)×0.25m
防护等级 Protection Degree	IP54

• XF-86




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO×2
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-87





材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO×2
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-88




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-89




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO×2
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-90




材 质 Material	铝合金(Aluminium)
内置开关 Inner Switch	慢动型(Slow Action Type)
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1NC1NO
引出电缆 Outgoing Cable	--
防护等级 Protection Degree	IP65

• XF-91




材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm²×3芯(Wire)×1m
防护等级 Protection Degree	IP54

• XF-92



材 质 Material	ABS工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	0.5mm²×3芯(Wire)×1m
防护等级 Protection Degree	IP54

• XF-93



材 质 Material	PA66工程塑料(Plastic)
内置开关 Inner Switch	XV-15-1C25
额定负载 Rating Load	10A/250VAC
触点形式 Contact Form	1C
引出电缆 Outgoing Cable	RJ-11×2m
防护等级 Protection Degree	IP54