

S-2000W Single output power supply



Summary

Single output: power 2000W
Input voltage: 200~264VAC



General Specification

291×132×68mm

Specification \ Model	S-2000-24	S-2000-27	S-2000-36	S-2000-48
DC output voltage, current	24V 0 ~ 83A	27V 0~74A	36V 0~55A	48V 0~41A
Wave and noise	120mVp-p	200mVp-p	200mVp-p	240mVp-p
Inlet wire stability	±0.5%	±0.5%	±0.5%	±0.5%
Load stability	±0.5%	±0.5%	±0.5%	±0.5%
Efficiency	80%	85%	86%	87%
Adjustable range for DC voltage	±10%	±10%	±10%	±10%
Input voltage range	200~264VAC			
Impact current	Cold start current 45A/230VAC			
Overload protection	105%~135% cut off the output, automatic recovery			
Setup, rise, hold up time	2000ms, 50ms, 20ms/230VAC at full load			
Withstand voltage	I/P-O/P: 1.5kV I/P-FG: 1,5kV O/P-FG: 0.5kV 1 minute			
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 500VDC/100M Ω			
Working temperature	-10°C~+50°C			
Dimension	291×132×136mm			
Weight	5.3kg			
Packing	38×37.5×21 CM/2PCS/11kg			

Overall dimension (mm)

