

S-3000W Single output power supply



Summary

Single output: power 30'00W
Input coltage: 200~264VAC



General Specification

291×132×68mm

Specification	Model	S-3000-24	S-3000-27	S-3000-36	S-3000-48
DC output voltage, current		24V 0 ~ 125A	27V 0~111A	36V 0~83A	48V 0~62.5A
Wave and noise		120mVp-p	200mVp-p	200mVp-p	240mVp-p
Inlet wire stability		±0.5%	±0.5%	±0.5%	±0.5%
Load stability		±0.5%	±0.5%	±0.5%	±0.5%
Efficiency		80%	85%	86%	87%
Adjustable range for DC voltage		±10%	±10%	±10%	±10%
Input voltage range		200~264VAC			
Impact current		Cold start current 45A/230VAC			
Overload protection		105%~135% cut off the output, automatic recovery			
Setup, rise, hold up time		2000ms, 50ms, 20ms/230VAC at full load			
Withstand voltage		I/P-O/P: 1.5kV I/P-FG: 1,5kV O/P-FG: 0.5kV 1 minute			
Isolation resistance		I/P-O/P I/P-FG O/P-FG: 500VDC/100M Ω			
Working temperature		-10°C~+50°C			
Dimension		291×132×136mm			
Weight		5.3kg			
Packing		38×37.5×21 CM/2PCS/11kg			

Overall dimension (mm)

